



FOR ADDED PROTECTION

- PROVIDE 4" DEEP WOOD CHIP MULCH OVER ANY UNPROTECTED ROOT ZONE.
- MAKE CLEAN CUTS ON ROOTS EXPOSED BY GRADING AND BACKFILL IMMEDIATELY.
- PROVIDE TEMPORARY IRRIGATION WHERE PRACTICAL AND FEASIBLE.

1. A TREE PRESERVATION/REMOVAL PERMIT APPLICATION MUST BE SUBMITTED AND APPROVED.
2. A LANDSCAPING PLAN SHALL BE SUBMITTED TO THE CITY FOR APPROVAL.
3. PROVIDE TIMBER WRAP PROTECTION FOR TREES WHEN WORK IS REQUIRED WITHIN CONSTRUCTION FENCING.
4. INSTALL VERTICAL 5 TO 6 FOOT LONG 2 BY 4's OR 2 BY 5's, SPACED 3 TO 5 INCHES APART, AROUND CIRCUMFERENCE OF TREE TRUNK.
5. FOR TREES OR SHRUBS IN PAVED AREAS, USE MOVABLE POSTS CONSISTING OF 2 1/2" MINIMUM DIAMETER CONCRETE FILLED STEEL PIPE MOUNTED IN RUBBER AUTOMOBILE TIRES WITH CONCRETE.